



UDY 80B



Print method

Paper width

Weight (g)

Dot per time

Print Speed Life Cycle time

Interface

self-check Commands

paper cut

Power

Max Diameter of paper Roll

Text & Graphic Support

Dot Pitch (resolution)

Recharge adapter

Black Mark test

Operate-setting

Recharge Setting Storage Setting

Standard Accessories















Waterproof

Oil proof

CERTIFICATION









111*124*48mm (W*D*H)

80mm Print width: 72 mm

(CODE39EAN13EAN8 CODABARCODE128CDE93ITF)

Stand by recharging / AC adapter

without paper / low power / cover open

ESC/POS compatible with order sets

Line thermal Printer

320g

45mm

576 dots/line 80mm's

203DPI/8 dots/mm

Supported

Tear bar



Long Tem Preservable Paper, AC adapter, USB cable

50km(printing density under 12.5%) 100 million pluses English, Figure, symbol chinese Graph, curve, icon pre-stored, barcode

RS232/Mini USB bluetooth Support android and ios

2600mAh 7.4V rechargeable Lithium Battery

Temperature 10°C~50°C; Humidity: 20%~85%

Temperature 5°C~40°C; Humidity: 20%~85%

Temperature 20°C~70°C; Humidity: 5%~95%

Serial interface cable / leather coat







Saxena Technologies India Pvt Ltd





